

Französischer
Hersteller seit
1964

www.gys.fr



AUSWAHL DER RICHTIGEN DRAHTROLLEN

B. Rollentypen je nach Schweißgerät

PRODUKT	Rollentyp	Anz. Rollen	Antriebsrollen	Rillentyp	Fülldraht				Volldraht stahl / edelstahl					Volldraht Alu				Drahtspule MIG / MAG		
					0.6	0.9-1.0	1.2	1.6	2.0	2.4	0.6	0.8	1.0	1.2	1.6	0.8	1.0	1.2	1.6	Ø100
SMARTMIG																				
142	A	2	1	35°V - 0.6 / 0.8																
152	A	2	1	35°V - 0.6 / 0.8																
162	A	2	1	35°V - 0.6 / 0.8																
182	A	2	1	35°V - 0.6 / 0.8																
MONOGYS																				
200-4CS	A	4	2	35°V - 0.8 / 1.0																
250-4CS	B	4	2	35°V - 0.8 / 1.0																
320-4CS	B	4	2	35°V - 1.0 / 1.2																
EASYMIG																				
85	D	2	1	90°V gerippt - 0.6 / 0.9																
130	D	2	1	35°V - 0.8 / 90°V gerippt - 0.9																
150	A	2	1	35°V - 0.8 / 90°V gerippt - 0.9																
160	A	2	1	35°V - 0.8 / 90°V gerippt - 0.9																
MULTIPEARL																				
210-2	A	2	1	35°V - 0.6 / 0.8																
210-4 XL	B	4	2	35°V - 0.6 / 0.8																
211-4	B	4	2	35°V - 0.6 / 0.8																
MULTIWELD																				
180M-C	A	4	2	35°V - 0.8 / 90°V gerippt - 0.9																
200M	A	2	1	35°V - 0.8 / 1.0																
200M-C	A	4	2	35°V - 0.8 / 1.0																
FV 220M-C	A	4	2	35°V - 0.8 / 1.0																
250T-C	A	4	2	35°V - 0.8 / 1.0																
320T-C	B	4	2	35°V - 0.8 / 1.0																
200M	A	4	2	35°V - 0.8 / 1.0																
FV 220M	A	4	2	35°V - 0.8 / 1.0																
250T	A	4	2	35°V - 0.8 / 1.0																
320T	B	4	2	35°V - 0.8 / 1.0																
400T	B	4	2	35°V - 1.0 / 1.2																
KRONOS																				
250M	B	4	2	35°V - 0.8 / 1.0																
320T	B	4	2	35°V - 1.0 / 1.2																
400T Duo	B	4	2	35°V - 1.0 / 1.2																
400T W	B	4	2	35°V - 1.0 / 1.2																
GALAXY																				
250M	B	4	2	35°V - 0.8 / 1.0																
250T	B	4	2	35°V - 1.0 / 1.2																
320T	B	4	2	35°V - 1.0 / 1.2																
400T Duo	B	4	2	35°V - 1.0 / 1.2																
400T W	B	4	2	35°V - 1.0 / 1.2																
WF																				
35 / 36	B	4	2	35°V - 1.0 / 1.2																
50	F	4	4	35°V - 1.0 / 1.2																
EXAGON																				
EXAFEEED-4L	C	4	2	35°V - 1.0 / 1.2																
NOMADFEED 425-4 CC/CV	E	4	2	35°V - 1.6																
	C			35°V - 1.2 / 1.6																
NEOPULSE																				
220 C	B	4	2	35°V - 0.8 / 1.0																
220 C XL	B	4	2	35°V - 0.8 / 1.0																
320 C	F	4	4	35°V - 1.0 / 1.2																
400 CW	F	4	4	35°V - 1.0 / 1.2																
400 G	F	-	-	-																
500 G	F	-	-	-																
NEOFEEED-4W	F	4	4	35°V - 1.0 / 1.2																
SMARTFEED M-4	F	4	4	35°V - 1.0 / 1.2																
E GYS AUTO																				
E1	B	4	2	35°V - 0.6 / 0.8																
E2	B	4 (x2)	2	U - 0.8 / 1.0																
				35°V - 0.6 / 0.8																
E3	B	4 (x3)	2	U - 0.8 / 1.0																
				35°V - 0.6 / 0.8																
P GYS AUTO																				
P1	B	4	2	U - 1.0 / 1.2																
P2	B	4 (x2)	2	U - 1.0 / 1.2																
				35°V - 0.8 / 1.0																
P3	B	4 (x3)	2	U - 1.0 / 1.2																
				35°V - 0.8 / 1.0																
AUTOPULSE																				
220-M1	B	4	1	U - 1.0 / 1.2																
220-M3	B	4 (x3)	2	35°V - 0.6 / 0.8																
				35°V - 0.8 / 1.0																
				U - 1.0 / 1.2																
320-T1	B	4	4	U - 1.0 / 1.2																
320-T3	B	4 (x3)		35°V - 0.6 / 0.8																
				35°V - 0.8 / 1.0																
				U - 1.0 / 1.2																