






# OSIGHT SE

## Simple yet Extraordinary

	Enclosed Emitter Optic		Aspherical Lens
	Side Load Battery	<b>7075</b>	Rugged 7075 Aluminum Housing
	RMSc Footprint		2 MOA Dot & 32 MOA Circle



# OSIGHT SE

Simple yet Extraordinary

## Market Applications

Concealed Carry, Self-Defense, Home Protection, Law Enforcement, Shooting Training

## UPC

6978095650155 (Osight SE)

## DESCRIPTION

The Osight SE is a compact yet powerful enclosed optic designed for concealed carry and tactical applications, enhancing your accuracy and confidence in every moment. It features a rugged 7075 aluminum housing and side load replaceable battery with low power indication for effortless maintenance. Its versatile multi-reticle system (2 MOA Dot, 32 MOA Circle, or both) offers precision shooting and rapid target acquisition. It boasts an aspherical lens for zero distortion and parallax-free performance, an ultra-low deck height for co-witnessing with most factory iron sights, and an RMSc footprint for direct mounting on optics-ready slides. Its robust construction and intelligent design make it the ideal choice for professionals demanding uncompromising performance.



# OSIGHT SE

Simple yet Extraordinary

---


## FEATURES

---

- **Enclosed Emitter Optic:** Designed with a fully sealed system, the optic offers unmatched protection against environmental elements.
- **Aspherical Lens:** Its aspherical lens ensures zero distortion and parallax-free performance, delivering exceptional clarity through the large window for rapid and precise target acquisition.
- **Side Load Battery:** Effortless battery replacement without removing the optic ensures hassle-free re-zeroing.
- **Readily Available CR1620 Battery:** A high-end CR1620 battery features easy accessibility but still offers steady performance.
- **RMSc Footprint:** Fitting directly to your optics-ready slides, the compact optic delivers exceptional compatibility, ensuring seamless integration across a multitude of builds.
- **2 MOA Dot & 32 MOA Circle:** Switching between dot-and-circle, dot-only, or circle-only reticles, you can tailor your aiming solution to any shooting scenario. The sharp and bright dot-and-circle reticle provides a cutting-edge aiming experience.
- **Motion Sensor Function:** The motion sensor immediately powers up illumination when it senses the slightest movement and powers down after 3 minutes of inactivity to extend battery life.
- **Sleek Body Design:** Shaped into an integrated streamlined body, the optic optimizes strength and reliability for concealed carry and duty use.
- **Rugged 7075 Aluminum Housing Material:** The optic is nearly indestructible with CNC machined aircraft-grade 7075 aluminum housing, ensuring durability and a professional edge over time.
- **10 Brightness Settings:** 8 daylight and 2 night vision settings - compatible levels for versatility in any demands.
- **Low Power Indication:** Provides clear visual battery power alerts that you can make immediate and actionable responses without being disruptive.
- **Low Profile:** Minimal and hidden, the logo on the optic is machined with 650 precision cuts using hard diamond blades.

## RUNTIME

---

			
Mode 3	46,600 H	75,000 H	50,000 H

# OSIGHT SE

Simple yet Extraordinary

## SPECIFICATIONS

Optic	Osight SE
Reticle Type	2 MOA Dot & 32 MOA Circle
Reticle Color	Red
Light Wavelength	650 nm
Adjustment Per Click	1 MOA
W&E Travel Range	± 35 MOA
Max. Runtime	75,000 H (Mode 3 Dot only)
Battery	CR1620
Brightness Setting	8 DL & 2 NV
Window Size	0.83 x 0.55 in 21 x 14 mm
Magnification	1x
Parallax Free	Yes
Unlimited Eye Relief	Yes
Motion Sensor Function	Yes
Memory Function	Yes
Multi-Coatings	Yes
Housing Material	7075 Aluminum
Waterproof Rating	IPX7
Dimensions	1.59 x 0.98 x 0.97 in 40.4 x 25 x 24.7 mm
Weight	0.97 oz / 27.5 g

## WARRANTY



[www.osight.com/lifetime-warranty](http://www.osight.com/lifetime-warranty)

## IN THE BOX

Optic (CR1620 battery included)  
Adjustment Tool  
READ ME card  
3 x M3\*10.5 mm Screw  
3 x M3\*11.5 mm Screw  
3 x M4\*9.4 mm Screw  
3 x M4\*10.5 mm Screw  
3 x #6-32\*0.433 in Screw  
3 x #6-40\*0.374 in Screw  
3 x #6-40\*0.449 in Screw  
2 x Battery Compartment Screw  
Screw Box  
Cleaning Cloth  
User Manual



Note: The Osight SE MUST be mounted properly by applying non-permanent (medium/blue) threadlocker to the included screws. AND torque each screw to 15-17 in-lbs (suggested torque value in the READ ME card). If an adapter plate is required, please follow the manufacturer's installation instructions.

## ⚠ WARNING


- **INGESTION HAZARD:** This product contains a button cell or coin battery.
- **DEATH** or serious injury can occur if ingested.
- A swallowed button cell or coin battery can cause **Internal Chemical Burns** in as little as **2 hours**.
- **KEEP** new and used batteries **OUT OF REACH** of CHILDREN.
- **Seek immediate medical attention** if a battery is suspected to be swallowed or inserted inside any part of the body.



(OPTIC)  
WATERPROOF  
IPX7



COMPLIANCE  
CAN ICES-003 (B) / NMB-003 (B)



[www.osight.com](http://www.osight.com)