

Reolink Argus Series

B330+Solar Panel Lite



5MP

5MP HD Resolution



Person, Vehicle & Animal Detection



120° Wide-Angle PIR



2.4GHz & 5GHz Dual Band WiFi6



Solar Unlimited Power



4-Month Battery Life



Easy & Flexible Wire-Free Installation



Local Encrypted Storage



Multi-User Management



One-Touch Privacy Mode



Instant Two-way Communication by Phone App



IP65 Weatherproof



AI Event Summary



Works with Google Assistant and Alexa



Home Hub Mini Integration



Timelapse Album

Reolink IPC Specifications

Categories	Parameters	Contents
Video & Audio	Image Sensor	1/2.7" CMOS sensor
	Resolution	2880 x 1616 @ 15 fps
	Lens	2.8mm/ F1.6 IR Cut
	Video Compression	H.264/H.265
	Field of View	Diagonal: 132°
		Horizontal: 110°
		Vertical: 58°
	Infrared Night Vision	6pcs, 850nm
	Color Night Vision	2pcs, 6500K
	Frame Rate	Up to 15fps
Audio	Two-way audio	
Power Requirements	Battery Capacity	5200mAh rechargeable battery
	Solar	Reolink Solar Panel Lite (2W)
Pan & Tilt	Auto-Tracking	NO
Bluetooth	Bluetooth Standard	Bluetooth V5.0
Interface	Power Port	USB Type-C Port (*Support USB-A to USB-C cable only.)
	SD Card Slot	Supports Max. 512GB microSD card
	Audio In/Out	Built-in microphone and speaker
Wi-Fi	Wireless Standard	IEEE 802.11 a/b/g/n/ac
	Operating Frequency	2.4GHz/5GHz
	Wireless Security	WPA/WPA2
Software	OS Supported	PC: Windows, macOS; Smartphone: iOS, Android
	Protocols & Standards	SSL, TCP/IP, UDP, UPNP, SMTP, NTP, P2P
Other Features	Smart Alarm	PIR detection, motion detection, person detection, vehicle detection, animal detection
	PIR Detecting Distance	Adjustable, up to 10m (33ft)
	PIR Detecting Angle	120° horizontal
	Recording Modes	Motion recording
	Time Lapse	YES
	Smart Home Compatibility	Google Assistant, Alexa
	Home Hub Compatibility	YES
	Cloud Storage	Supports Reolink Cloud (available in selected countries)
Working Environment	Operating Temperature	-20°C~55°C (14°F~131°F)
	Operating Humidity	20% ~ 85%
	Weatherproof	IP67
Mechanical	Dimensions	67.6*56*90.5mm
	Weight	218g (Does not include bracket)
Warranty	Weight	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/ .

Reolink Solar Panel Specifications

Model	Model	SR8
	Name	Reolink Solar Panel Lite
Size & Weight	Dimensions	110.6 x 93.1 x 11 (mm)
	Cable Length	270 mm
	Weight	79g
	Interface	USB Type-C Port
Electrical Parameters	Standard Operating Voltage	5.4V \pm 5%
	Standard Operating Current	375mA \pm 5%
	Output Power	\geq 1.9W
Other	Working Temperature	-10 $^{\circ}$ C ~ +55 $^{\circ}$ C (14 $^{\circ}$ F ~ 131 $^{\circ}$ F)
	Working Humidity	10%~90%
	Waterproof	IP65
	Extension Cable Supported	Maximum 2 Extension Cable (USB-C)