



Reolink Innovation Limited.

Picture



Model

Go Series G430

Video & Audio

Image Sensor	1/3" CMOS Sensor
Video Resolution	2880 x 1620 (5.0Megapixel) at 15 frames/sec
Video Format	H.265
Field of View	Fixed lens, Horizontal: 90°, Vertical: 47°, 110° diagonal
Infrared Night Vision	up to 10 Meters (33ft) (LED: 2pcs/1.2W/850nm)
Spotlight	2pcs/2.4W/6500K/
Digital Zoom	16x digital zoom
Audio	two-way audio

PIR Detection & Alerts

Smart Alarm	PIR detection/Human Detection/Vehicle Detection/Animal Detect
PIR Detecting Distance	Adjustable up to 10m (33 ft)
PIR Detecting Angle	120° horizontal
Audio Alert	Customized verbal alerts
Recording	Motion Triggered Recording
Other Alerts	Instant email alerts and push notifications

3G/4G

Frequency Bands	Europe	LTE FDD: B1/B3/B7/B8/B20/B28A
		WCDMA: B1/B8
	America	LTE FDD: B2/B4/B5/B12/B13/B14/B66/B71
		WCDMA: B2/B4/B5
	Australia	LTE FDD: B1/B3/B5/B7/B8/B28
		LTE TDD: B40
WCDMA: B1/B5/B8		
Transmission Data		LTE FDD: Max 10Mbps(DL), Max 5Mbps(UL)
		LTE TDD: Max 8.96Mbps(DL), Max 3.1Mbps(UL)
		HSPA+: Max 42Mbps(DL), Max 5.76Mbps(UL)
		UMTS: Max 384Kbps(DL), Max 384Kbps(UL)

Power

Battery	6000mAh rechargeable battery (Battery life varies based on settings, usage & temperature)
Solar	Reolink Solar Panel
DC Power	5V/2A USB power adaptor

Storage

Local Storage	Supports up to 128GB micro SD card
Cloud Storage	Supports Reolink Cloud

Smart Home

Smart Home	Works with Google Assistant
------------	-----------------------------

Working Environment

Operating Temperature	-10 to 55° C (14° to 131° F)
Weather Resistance	IP64 Weatherproof

Size & Weight

Size	Φ98 x 122mm (Φ3.7 x 4.4 in)
Weight (Battery included)	485 g (17.1 oz)

Warranty

Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
------------------	---