

Picture

Model
P334
Video & Audio

Image Sensor	1/2.49" CMOS Sensor
Video Resolution	Default: 3840 x 2160 (8.0 Megapixels) at 25 frames/sec
Lens	f=2.8mm fixed, F=1.6, with IR Cut
Video Format	H.265
Field of View	Horizontal: 105°
	Vertical: 56°
Day & Night	IR-cut filter with auto-switching
Infrared LED	30 Meters (100 ft) (LED: 2pcs/1.8W/850nm)
Spotlight	1pcs/4.3W/6500K/ 700Lumens
Audio	Built-in Microphone and Speaker

Power

POE	IEEE 802.3af, 48V Active
DC Power	DC 12.0V=1A, <12W

Interface

Power	DC power port
System	Reset Button
Ethernet	One 10M/100Mbps RJ45
Storage	MicroSD card slot (Max. 256GB)

Software Features

Frame Rate	Main Stream: 2fps - 25fps(default: 25fps)
	Sub Stream: 4fps - 15fps(default: 10fps)
Code Rate	Main Stream: 2048Kbps -8192Kbps(default: 6144Kbps)
	Sub Stream: 64Kbps - 512Kbps(default: 256Kbps)
Browser Supported	IE, Edge, Chrome, Firefox, Safari
OS Supported	PC: Windows, Mac OS; Smartphone: iOS, Android
Smart Alarm	Motion detection/Human Detection/Vehicle Detection/Pet Detection
Record Mode	Motion Record/Schedule Record (Default: Motion Record)
Protocols & Standards	HTTPS, SSL, TCP/IP, UDP, HTTP, IPv4, UPnP, RTSP, RTMP, ONVIF, SMTP, NTP, DHCP, DNS, DDNS, FTP, P2P
Maximal User Access	20 Users (1 admin account & 19 user accounts); Support up to 12 simultaneous video streams (10 substreams & 2 mainstreams)
Work with	Google Assistant, Reolink NVR

Working Environment

Temperature	Operating Temperature: -10°C~+55°C (14°F~131°F)
Humidity	Operating Humidity: 10% ~ 90%
Waterproof	IP 66

Size & Weight

Dimension	Φ117.4 x 103.8mm
Weight	526g

Warranty

Limited Warranty	2-year limited warranty. For support, visit https://support.reolink.com/hc/en-us/
------------------	---