


Geberit Mepla Reduktion



Verwendungszweck

- Verwendungsübersicht: Geberit Mepla

Eigenschaften

- Unverpresst undicht
- O-Ring aus EPDM
- Pressnippel mit transparenter Schutzkappe

Technische Daten

Werkstoff

PVDF

Artikel

Art.-Nr.	NPK-Nr.	DN	d, ø [mm]	d1, ø [mm]	L [cm]	Z [cm]
622.650.00.5	254.322	15 / 12	20	16	7.1	1.6
623.650.00.5	254.323	20 / 12	26	16	7.5	1.6
623.651.00.5	254.323	20 / 15	26	20	7.8	1.6
624.651.00.5	254.324	25 / 15	32	20	8.5	1.8
624.652.00.5	254.324	25 / 20	32	26	8.5	1.4
625.651.00.5	254.325	32 / 15	40	20	9	1.8
625.652.00.5	254.325	32 / 20	40	26	9.2	1.5
625.653.00.5	254.325	32 / 25	40	32	9.7	1.5
626.652.00.5	254.326	40 / 25	50	32	10.3	1.5
626.653.00.5	254.326	40 / 32	50	40	11.1	1.7
627.653.00.5	254.327	50 / 32	63	40	13.1	1.9
627.654.00.5	254.327	50 / 40	63	50	13.7	2
628.653.00.5	254.328	65 / 32	75	40	15.2	2.1
628.654.00.5	254.328	65 / 40	75	50	15.8	2.1
628.655.00.5	254.328	65 / 50	75	63	17.6	2.1