


Geberit Mepla T-Stück mit Innengewinde



Verwendungszweck

- Verwendungsübersicht: Geberit Mepla

Eigenschaften

- Unverpresst undicht
- O-Ring aus EPDM
- Pressnippel mit transparenter Schutzkappe

Technische Daten

Werkstoff

Rotguss (CuSn5Zn5Pb2-C)

Artikel

Art.-Nr.	NPK-Nr.	DN	d, ø [mm]	Rp ["]	d1, ø [mm]	L [cm]	L1 [cm]	Z [cm]	Z1 [cm]
601.360.00.5	253.171	12 / 1/2 / 12	16	1/2	16	9.8	2.4	2.4	0.9
602.360.00.5	253.172	15 / 1/2 / 15	20	1/2	20	10.3	2.4	2.4	1.1
603.360.00.5	253.173	20 / 1/2 / 20	26	1/2	26	11.2	2.6	2.4	1.3
603.362.00.5	253.173	20 / 3/4 / 20	26	3/4	26	11.8	2.8	2.7	1.4
604.360.00.5	253.174	25 / 1/2 / 25	32	1/2	32	10.6	3	2.5	1.7
604.362.00.5	253.174	25 / 3/4 / 25	32	3/4	32	11.2	3.1	2.8	1.7
604.363.00.5	253.174	25 / 1 / 25	32	1	32	12	3.5	3.2	1.8
605.360.00.5	253.175	32 / 1/2 / 32	40	1/2	40	12	3.2	2.6	1.7
605.363.00.5	253.175	32 / 1 / 32	40	1	40	13.2	3.8	3.2	2.1
605.364.00.5	253.175	32 / 1 1/4 / 32	40	1 1/4	40	14.4	4	3.8	2.1
606.361.00.5	253.176	40 / 1/2 / 40	50	1/2	50	13.2	3.8	2.8	2.3
606.363.00.5	253.176	40 / 1 / 40	50	1	50	14.6	4.4	3.5	2.5
606.360.00.5	253.176	40 / 1 1/2 / 40	50	1 1/2	50	16.6	4.5	4.5	2.6
607.360.00.5	253.177	50 / 1/2 / 50	63	1/2	63	19.2	4.2	2.9	2.7
607.363.00.5	253.177	50 / 1 / 50	63	1	63	20.6	4.8	3.6	2.9
607.366.00.5	253.177	50 / 2 / 50	63	2	63	23.8	5.7	5.2	3.1
608.363.00.5	253.178	65 / 1 / 65	75	1	75	26.1	5.1	4.4	2.9