

K950707LPR01MAET
60X120 CEMENTINE MINK 7LPR 2Q



VitrA

Surface Technology / Oberflächentechnik / Yüzey Teknolojisi
Technologie de surface / Поверхностные технологии / سطح / تكنولوجيا

Compliant with EN 14411:2016(ISO 13006)
EN 14411 - Group B1a, Annex G
thickness ≥ 7.5mm

Unglazed /Unglasiert/Sırsız /Non Emailé/
Herlazurolanmış / غير مطلي/ غير مغطى



9mm

| Technical Features / Technische Eigenschaften / Teknik Özellikler |                                                                                                                                                                                                                           |                                                                                                                                                                                                        | Test Method/Prüfmethode/<br>Test Yöntemi/Méthode d'essai/<br>Метод испытания / طريقة اختبار | Standard Values         | VitrA Tiles Product Values                                                                                                                                                                              |
|-------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|-------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                                   | DE Länge und Breite<br>FR Longueur et largeur<br>TR Uzunluk ve Genişlik                                                                                                                                                   | EN Length and Width<br>RU длина и ширина<br>AR الطول والعرض                                                                                                                                            | EN ISO 10545-2                                                                              | max. ± 0,6 % and ±2,0mm | max. ± 0,6 % and ±2,0mm                                                                                                                                                                                 |
|                                                                   | DE Dicke<br>FR Epaisseur<br>TR Kalınlık                                                                                                                                                                                   | EN Thickness<br>RU толщина<br>AR السمك                                                                                                                                                                 |                                                                                             | max. ± 5 % and ±0,5mm   | max. ± 5 % and ±0,5mm                                                                                                                                                                                   |
|                                                                   | DE Geradheit der Kanten<br>FR Rectitude des Aretes<br>TR Kenar Eğriliği                                                                                                                                                   | EN Straightness of Sides<br>RU Прямолинейность<br>AR استقامة الجوانب                                                                                                                                   |                                                                                             | max. ± 0,5 % and ±2,0mm | max. ± 0,5 % and ±2,0mm                                                                                                                                                                                 |
|                                                                   | DE Rechtwinkligkeit<br>FR Rectangularité<br>TR Dikdörtgenlik                                                                                                                                                              | EN Rectangularity<br>RU Прямоугольность<br>AR التعامد                                                                                                                                                  |                                                                                             | max. ± 0,5 % and ±2,0mm | max. ± 0,5 % and ±2,0mm                                                                                                                                                                                 |
|                                                                   | DE Oberflächenebenheit (Mitte und Rand)<br>FR Planéité de Surface (Centre et Edge)<br>TR Yüzey Düzgünlüğü (Merkez ve Kenar)                                                                                               | EN Surface Flatness (Center and Edge)<br>RU Поверхностная плоскостность (Центр и края)<br>AR استقامة السطح ( المركز و الأطراف )                                                                        |                                                                                             | max. ± 0,5 % and ±2,0mm | max. ± 0,5 % and ±2,0mm                                                                                                                                                                                 |
|                                                                   | DE Oberflächenebenheit (Ecke)<br>FR Planéité de surface (Coin)<br>TR Yüzey Düzgünlüğü (Köşe)                                                                                                                              | EN Surface Flatness (Warpage)<br>RU Поверхностная плоскостность (Искривление)<br>AR استقامة السطح ( الزايات )                                                                                          |                                                                                             | max. ± 0,5 % and ±2,0mm | max. ± 0,5 % and ±2,0mm                                                                                                                                                                                 |
|                                                                   | DE Oberflächenbeschaffenheit<br>FR Qualité de Surface<br>TR Yüzey Kalitesi                                                                                                                                                | EN Surface Quality<br>RU Качество поверхности<br>AR جودة السطح                                                                                                                                         |                                                                                             | min. 95 %               | min. 95 %                                                                                                                                                                                               |
|                                                                   | DE Wasseraufnahme<br>FR Absorption d'eau<br>TR Su Emme                                                                                                                                                                    | EN Water Absorption<br>RU водопоглощение<br>AR امتصاص الماء                                                                                                                                            | EN ISO 10545-3                                                                              | Avg. ≤ 0,5 %            | Avg. ≤ 0,5 %                                                                                                                                                                                            |
|                                                                   | DE Bruchlast<br>FR Force de Rupture<br>TR Kırılma Dayanımı                                                                                                                                                                | EN Breaking Strength<br>RU Разрушающая нагрузка<br>AR تحمل عند الكسر                                                                                                                                   | EN ISO 10545-4                                                                              | > 1300 N                | >1300N                                                                                                                                                                                                  |
|                                                                   | DE Biegefestigkeit<br>FR Résistance à la flexion<br>TR Eğilme Dayanımı                                                                                                                                                    | EN Modulus of Rupture<br>RU Прочность на изгиб<br>AR تحمل عند الانحناء                                                                                                                                 |                                                                                             | > 35 N/mm²              | > 35 N/mm²                                                                                                                                                                                              |
|                                                                   | DE Widerstand gegen Tiefenverschleiß<br>FR Résistance à l'abrasion Profonde<br>TR Derin Aşınma                                                                                                                            | EN Deep Abrasion<br>RU Соппротивление к глубокому истиранию<br>AR المقاومة ضد التآكل العميق                                                                                                            | EN ISO 10545-6                                                                              | < 175 mm³               | < 175 mm³                                                                                                                                                                                               |
|                                                                   | DE Widerstand gegen Oberflächenverschleiß<br>FR Résistance à l'abrasion PEI<br>TR Yüzey Aşınma (PEI)                                                                                                                      | EN Surface Abrasion (PEI)<br>RU Устойчивость к истиранию<br>AR المقاومة ضد تآكل السطح                                                                                                                  | EN ISO 10545-7                                                                              | Not Applicable          | Not Applicable                                                                                                                                                                                          |
|                                                                   | DE Linearer Wärmeausdehnungskoeffizient<br>FR Coeff. de dilatation therm. Maxi<br>TR Lineer Isıl Genleşme                                                                                                                 | EN Linear Thermal Expansion<br>RU Линейный коэффициент теплового расширения<br>AR التمدد الحراري للنظام                                                                                                | EN ISO 10545-8                                                                              | Declared Value          | max. 8 X 10 <sup>-6</sup> K <sup>-1</sup>                                                                                                                                                               |
|                                                                   | DE Temperaturwechselbeständigkeit<br>FR Résistance aux écarts de température<br>TR Isı Sokuna Dayanım                                                                                                                     | EN Thermal Shock Resistance<br>RU Термостойкость<br>AR مقاومة الصدمات الحرارية                                                                                                                         | EN ISO 10545-9                                                                              | Confirmed               | Confirmed                                                                                                                                                                                               |
|                                                                   | DE Widerstand gegen Glassprünge<br>FR Résistance au tressailage<br>TR Catlama Dayanıklılığı                                                                                                                               | EN Cracking Resistance<br>RU Устойчивость к растрескиванию<br>AR مقاومة التشقق                                                                                                                         | EN ISO 10545-11                                                                             | Not Applicable          | Not Applicable                                                                                                                                                                                          |
|                                                                   | DE Frostbeständigkeit<br>FR Résistance au gel<br>TR Don Dayanımı                                                                                                                                                          | EN Frost Resistance<br>RU морозостойкость<br>AR مقاومة التجمد                                                                                                                                          | EN ISO 10545-12                                                                             | Confirmed               | Confirmed                                                                                                                                                                                               |
|                                                                   | DE Feuchtigkeitsdehnung<br>FR Dilatation à l'humidité<br>TR Rutubet Genleşmesi (mm/m)                                                                                                                                     | EN Moisture expansion<br>RU Набухание<br>AR التمدد بالرطوبة                                                                                                                                            | EN ISO 10545-10                                                                             | Declared Value          | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Kleine Farbabweichungen (Für einfarbige)<br>FR Faibles différences de couleur (Pour couleur clair)<br>TR Küçük Renk Farklılıkları(Düz renkler için)                                                                    | EN Small colour differences (For plain coloured)<br>RU Небольшие различия цвета (Для простой цвет)<br>AR اختلافات اللون البسيط ( لسطح اللونية )                                                        | EN ISO 10545-16                                                                             | Not Applicable          | Not Applicable                                                                                                                                                                                          |
|                                                                   | DE Schlagfestigkeit<br>FR Résistance aux chocs<br>TR Çarpma Dayanımı                                                                                                                                                      | EN Impact resistance<br>RU Ударопрочность<br>AR مقاومة الصدمات                                                                                                                                         | EN ISO 10545-5                                                                              | Declared Value          | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Verbundfestigkeit (zementhaltige)<br>FR Adhésion (ciment colle)<br>TR Yapışma Dayanımı                                                                                                                                 | EN Bond Strength (cementitious adhesives)<br>RU Плотность прилегания<br>AR قوة التماسك مع الأسفل المصنعت ي                                                                                             | EN 12004                                                                                    | Declared Value          | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Brandverhalten<br>FR Réaction au feu<br>TR Ateşe Dayanıklılık                                                                                                                                                          | EN Reaction to fire<br>RU Пожаростойкость<br>AR رد الفعل على الحريق اتي                                                                                                                                | -                                                                                           | Class A1 or A1fl        | Class A1fl                                                                                                                                                                                              |
|                                                                   | DE Fleckbeständigkeit<br>FR Résistance aux taches<br>TR Lekelenmeye Dayanım                                                                                                                                               | EN Staining Resistance<br>RU Стойкость к окрашиванию<br>AR مقاومة البقع                                                                                                                                | EN ISO 10545-14                                                                             | Declared Value          | min. Class 3                                                                                                                                                                                            |
|                                                                   | DE Beständigkeit gegen Haushaltschemikalien und Badewasserzusätze (Schwimmbecken)<br>FR Résistance aux produits chimiques ménagers et aux additifs de l'eau du bain<br>TR Ev Kimyasalları ve Havuz Tuzlarına Dayanıklılık | EN Resistance to household chemicals and swimming pool salts<br>RU Устойчивость к бытовым химическим продуктам и средствам для бассейнов<br>AR المقاومة للمواد الكيميائية المنزلية وأحماض حمام السباحة | EN ISO 10545-13                                                                             | min. Class B            | min. Class B                                                                                                                                                                                            |
|                                                                   | DE Chemische Beständigkeit (*)<br>FR Résistance chimique (*)<br>TR Kimyasal Dayanım (*)                                                                                                                                   | EN Chemical Resistance (*)<br>RU Химическая устойчивость (*)<br>AR (*) مقاومة كيميائية                                                                                                                 |                                                                                             | Declared Value          | LA - LC<br>HA - HC                                                                                                                                                                                      |
|                                                                   | DE Abgabe von Blei und Cadmium<br>FR Teneur en plomb et en cadmium<br>TR Ağır çıkan Kurşun ve Kadmilyum                                                                                                                   | EN Lead and Cadmium release<br>RU Выделение свинца и кадмия<br>AR الرصاص والكاديوم الصادر                                                                                                              | EN ISO 10545-15                                                                             | Declared Value          | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Ritzhärte (Moh's)<br>FR Dureté à la rayure (Moh's)<br>TR Yüzey Sertliği (Moh's)                                                                                                                                        | EN Scratch Hardness (Moh's)<br>RU Устойчивость к царапинам (Moh's)<br>AR مدى صلابة (مو )                                                                                                               | EN 101                                                                                      | •                       | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Farbresistenz gegen UV-Licht<br>FR Résistance des couleurs à la lumièreUV<br>TR UV ışığına Karşı Renk Dayanımı                                                                                                         | EN Colour Resistance to UV Light<br>RU Стойкость цвета к ультрафиолетовому излучению<br>AR مقاومة اللون لأشعة فوق البنفسجية                                                                            | DIN 51094                                                                                   | •                       | Resistant                                                                                                                                                                                               |
|                                                                   | DE Lichtreflexionswert (LRW)<br>FR La valeur de réflexion de la lumière (LRV)<br>TR Işıık Yansıtma Değeri (LRV)                                                                                                           | EN Light Reflectance Value (LRV)<br>RU коэффициент отражения света (LRV)<br>AR قيمة انعكاس الضوء (LRV)                                                                                                 | ASTM C609                                                                                   | •                       | No Performance Determined                                                                                                                                                                               |
|                                                                   | DE Rutschfestigkeit (**)<br>FR Glissance (**)<br>TR Kaymazlık (**)                                                                                                                                                        | EN Slipperiness (**)<br>RU Скользяность (**)<br>AR الزلاقي (**)                                                                                                                                        | DIN 51130<br>DIN 51097<br>BS 7976-2<br>BS 7976-2<br>BS 7976-2<br>BS 7976-2<br>ANSI A137.1   | Declared Value          | No Performance Determined<br>No Performance Determined<br>No Performance Determined<br>No Performance Determined<br>No Performance Determined<br>No Performance Determined<br>No Performance Determined |

\*Hydrofluoric acid and its compounds excluded. / Flussäure und deren Verbindungen ausgeschlossen. / Hidroflorik asit ve türevleri hariçtir.
L'acide fluorhydrique et ses composés sont exclus. / Полновое исключение и ее соединения исключены. / حمض الفلوروفوريك و مركباته مستبعد.
\*\*Anti-slip performance is guaranteed at the time of delivery of the product. / Die Rutschhemmung ist zum Zeitpunkt der Lieferung des Produkts garantiert. / Ürün teslimatındaki kaymazlık performansı
garanti edilir. / Эффективность против скольжения гарантируется во время доставки продукта. / يتم ضمان عدم الانزلاق في وقت تسليم المنتج.

